


LOGO ABOVE THE SURFACE 0.20mm



Frequency	Near-End Cross Talk dB, MIN.	Return Loss dB, MIN.	Attenuation dB, MAX.
1.0 MHZ	65.0	35.5	0.1
4.0 MHZ	65.0	35.5	0.1
8.0 MHZ	64.9	35.5	0.1
10.0 MHZ	63.0	35.5	0.1
16.0 MHZ	56.9	35.5	0.2
20.0 MHZ	57.0	34.0	0.2
25.0 MHZ	55.0	32.0	0.2
31.25 MHZ	53.1	30.1	0.2
62.5 MHZ	47.1	24.0	0.3
100.0 MHZ	43.0	20.0	0.4

MECHANICAL:

- 1. HOUSING MATERIAL : PC UL94V-0
- 2. INSERT MATERIAL : GLASS FILLED POLYESTER UL94V-0 BK.
- 3. PCB MATERIAL : FR-4 THICKNESS 1.6mm
- 4. CONTACT MATERIAL : PHOSPHOR BRONZE STAMP PIN t=0.35mm

ENVIRONMENTAL:

- 1. STORAGE: -40°C TO +85°C.
- 2. OPERATION: 0°C TO 70°C.
- CONFORMING TO TIA/EIA 568B
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

RoHS compliant
Unit: mm



Scale	Free TOLERANCE	Free TOL	Free Id.	Date	Name	Customer-No.
.X	±0.20			02.07.2013	Winnie	
.XX	±0.15			24.03.2017	Amy	ASSMANN WSW-No.
.XXX	±0.10					A-TA3534
DIM	TOL					ASSMANN WSW-No.
Angle	±5°					ASS 5822 CO
Angle	TOL					rev01

ASSMANN
WSW components

1 2 3 4 5 6 7

CON031