

**Industrial Ethernet
IE-PS-V01M-2LC-MM-BP**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Bayonet plug-in connector sets according to IEC
61076-3-106 ver.1 (EtherNet/IP), RJ45 metal insert incl.
LC insert

General ordering data

Type	IE-PS-V01M-2LC-MM-BP
Order No.	1963230000
Version	FO connector, Variant 1, LC-Duplex multi-mode, with kink prevention, IP 67
GTIN (EAN)	4032248651702
Qty.	10 pc(s).

Data sheet

**Industrial Ethernet
IE-PS-V01M-2LC-MM-BP**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 148.6 g

Temperatures

Operating temperature -40 °C...70 °C Storage temperature
 Installation temperature

Downloads

GOST Approval POCC
 DE.ME25.B01411.pdf

General data

Colour	Miscellaneous	Connection 1	LC
Connection 2	LC	Description of article	Variant 1, LC-Duplex multi-mode, with kink prevention
Fibre type	Multimode	Housing main material	Zinc diecast
Insertion loss	0.5 dB singlemode, 0.4 dB multimode	Plugging cycles	500
Protection degree	IP 67	Return loss (attenuation)	40 dB singlemode; 30 dB multimode
Sheath diameter, max.	10 mm	Sheath diameter, min.	5 mm

Standards

Connector standard IEC 61076-3-106 Var. 1,
 IEC 61754-20

Classifications

ETIM 3.0	EC001121	ETIM 4.0	EC002641
ETIM 5.0	EC002641	ETIM 6.0	EC002641
UNSPSC	30-21-18-10	eClass 5.1	27-26-07-08
eClass 6.2	27-26-07-08	eClass 7.1	27-25-05-04

Approvals

Approvals



ROHS Conform

Data sheet

**Industrial Ethernet
IE-PS-V01M-2LC-MM-BP**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Dimensioned drawing

